

SAFETY DATA SHEET

DRICORE™ PRO Concrete Repair High Strength Anchoring Epoxy Paste | Revision Date 09/30/2020

2311 Royal Windsor Drive Unit 2
Mississauga, Ontario, Canada L5J 1K5
P: +1 866 767 6374
E: info@dricore.com

01

01: PRODUCT & COMPANY IDENTIFICATION

Product Name: DRICORE™ PRO Concrete Repair High Strength Anchoring Epoxy Paste
Common Name: Polyamine
Company Address: 2311 Royal Windsor Drive Unit 2
Mississauga, Ontario, Canada L5J 1K5
P: +1 866 767 6374
E: info@dricore.com

Chemical Family: Polyamine
Synonyms: Amines Paste
Product Use: Epoxy Bonding Agent
Emergency Phone: CHEMTRAC 1 800 424 9300

02: HAZARDS IDENTIFICATION

GH Classification	CATEGORY
HEALTH HAZARD	1B
Skin Corrosion	1B
Eye damage	1
Skin Sensitizer	1
Acute Toxicity, Oral	4
Acute Toxicity, Inhalation	4
Aquatic Toxicity	3

Hazard Statement

Harmful if swallowed or inhaled. Causes severe skin burns and serious eye damage. May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects.

Precautionary Statement

Use only outdoors or in well ventilated area. Avoid breathing mist, vapors or spray. Wear protective clothing, gloves and eye and face protection. Wash skin thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment.

03: COMPOSITION / INFORMATION ON INGREDIENTS

Ingredients:

Cas#	Chemical Name	%	OSHA PEL	ACGUH TLV
Component A				
25085-99-8	Propane, 2,2-bis[p-(2,3-epoxypropoxy)phenyl]-, polymers	>40%	NE	NA
13463-67-7	Titanium Dioxide	<20%	NE	NE
1317-65-3	Calcium Carbonate	<30%	NE	NE
68611-44-9	Amorphous Silicon Dioxide	<10%	NE	NE
Component B				
6895-36-6	Polyamido amine	<40%	NE	NE
68611-44-9	Amorphous Silicon Dioxide	<10%	NE	NE
1317-61-9	Iron Oxide black	<10%	NE	NE
1317-65-3	Calcium Carbonate	>40%	NE	NE

None of the remaining components are considered a hazardous material or carcinogen (1910.1200 Hazard Communication (d) 4.)

NE= Not Established NA=Not Applicable

04: FIRST AID MEASURES

General Advice:	Seek medical advice. If breathing has stopped or is labored, give assisted respirations. Supplemental oxygen may be indicated. If the heart has stopped trained personnel should begin cardiopulmonary resuscitation immediately.
Inhalation:	If respiratory irritation occurs, go to fresh air, flood work area with fresh air. If irritation continues seek medical attention.
Skin Contact:	Remove contaminated clothing and shoes. Wash affected area(s) thoroughly with soap and water. If irritation persists, seek medical attention. SOLVENTS SHOULD NOT BE USED because they carry the irritant into the skin.
Eye Contact:	Flush the eyes with plenty of water for at least 15 minutes. If necessary, gently hold eyelids open during the flush. Immediately seek medical attention.
Ingestion:	Obtain immediate medical attention. Do not induce vomiting. Should vomiting occur, be sure to keep victim's head below hips to avoid aspiration of vomit into the lungs.

05: FIRE FIGHTING MEASURES

Special Fire Fighting Procedures: none. Avoid breathing smoke. NFPA Class B-C extinguisher (dry chemical or foam) for class 1C fires. Water spray may be ineffective on fire but can protect fire-fighters and cool closed containers. Use fog nozzles if water is used. Use supplied breathing masks.

Protection of firefighters: Fire may produce irritating, corrosive and/or toxic gases. Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots and in enclosed spaces SCBA. Structural firefighters protective clothing will only provide limited protection.



1-866-767-6374 | www.dricore.com

SAFETY DATA SHEET

DRICORE™ PRO Concrete Repair High Strength Anchoring Epoxy Paste | Revision Date 09/30/2020

2311 Royal Windsor Drive Unit 2
Mississauga, Ontario, Canada L5J 1K5
P: +1 866 767 6374
E: info@dricore.com

02

06: ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Keep people away from and upwind of spill/leak. Avoid inhalation of vapors and spray mists. Keep out of low areas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Follow facility/company's emergency plans.
Small Spills:	Absorb with an inert material (sand, vermiculite). Sweep or scoop up and put into disposal containers. Flush area immediately with water (prevent water from entering waterways).
Large Spills:	Dike area far ahead of liquid spill for later disposal. Do not release into sewers or waterways. Absorb with an inert material (sand, vermiculite). Sweep or scoop up into disposal containers. Flush area immediately with water (prevent water from entering waterways)
Regulatory Requirements: wearing	Follow applicable OSH regulations (29 CFR 1910.120). Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Persons not

07: HANDLING AND STORAGE

Handling Precautions:	For professional use only. Avoid eye/skin contact. Wash after using and before eating or smoking. Avoid breathing vapors. Use as directed. Avoid uncontrolled mixing with other mixtures (strong acids, bases and oxidizers). Do not use solvent to thin. Respiratory protection is required when ventilation is inadequate. NIOSH/OSHA approved respirators should be provided and worn.
Storage Requirements:	Store in cool/dry location. Do not allow material to freeze, as product may be damaged. Store away from sparks and open flames.

08: EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:	HMIS PP, H I Splash Goggles, Gloves, Apron, Vapor Respirator Use local and general exhaust ventilation to maintain airborne concentrations below TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it.
Personal Protective Equipment	RESPIRATORY PROTECTION: None normally required. Use a NIOSH approved organic vapor chemical cartridge respirator when air movement is inadequate to control vapor build-up. EYE/FACE PROTECTION: Wear splash proof chemical goggles/ full face shield if there is a potential for splashing. SKIN / BODY PROTECTION: Wear Suitable gloves (neoprene, nitrile rubber or PVC) and protective clothing to mitigate exposure. OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Use protective clothing which is chemical resistant to this material. Safety shoes and boots should also be chemical resistant.

09: PHYSICAL & CHEMICAL PROPERTIES

Appearance: CE308	Part A (white paste) CE308	Part B (black paste)	Percent Volatile:	0
Physical State	paste		Flash Point:	>200°F
Boiling Point:	ND		Flash Point Method:	Pensky Martens Closed Cup
Odor:	Part A (Mild)	Part B (Amine odor)	Burning Rate:	No data available
Freezing/Melting Point:	ND/NE		Autoignition Temp:	No data available
pH:	ND		LEL:	NA
Solubility:	Insoluble			
Vapor Pressure:	NE			
Vapor Density:	(Air = 1) > 1			
Spec Grav./Density:	Part A (1.2)	Part B (1.8)		
VOC:	0			
Evap Rate:	Slower than Butyl Acetate			
Viscosity:	Brookfield 500,000 cps (Part A), 500,000 cps (Part B)			

10: STABILITY AND REACTIVITY

Stability:	Stable
Conditions to Avoid:	None
Materials to Avoid:	Strong oxidizers, acids and bases
Hazardous Decomposition Products:	CO, CO2, NOX
Hazardous Polymerization:	None

11: TOXICOLOGICAL INFORMATION

Inhalation:	Harmful if inhaled and may cause delayed lung injury. Can cause severe respiratory tract burns. Risk of serious damage to the lungs. May cause nose, throat and lung irritation. Inhalation of vapors and/or aerosols in high concentration may cause irritation of respiratory system.
Skin Contact:	Causes skin burns.
Eye Contact:	Causes eye burns. May cause blindness. Severe eye irritation.
Ingestion:	If ingested, severe burns of the mouth and throat, as well as a danger of perforation of the esophagus and the stomach.
Prolonged exposure	Repeated and/or prolonged exposure to low concentrations of vapors and/or aerosols may cause: Sore throat, Eye disease, Skin Disorders and Allergies.

This product contains no listed carcinogens according to IARC, ACGIH, NTP and/or OSHA in concentrations of 0.1 percent or greater. Prolonged contact may result in chemical burns and permanent damage.



1-866-767-6374 | www.dricore.com

SAFETY DATA SHEET

DRICORE™ PRO Concrete Repair High Strength Anchoring Epoxy Paste | Revision Date 09/30/2020

2311 Royal Windsor Drive Unit 2
Mississauga, Ontario, Canada L5J 1K5
P: +1 866 767 6374
E: info@dricore.com

03

12: ECOLOGICAL INFORMATION

Aquatic toxicity Very toxic to aquatic organisms, may cause long term adverse effects in the
Toxicity to other organisms: No data available

13: DISPOSAL CONSIDERATIONS

When disposed of properly, this material does not meet RCRA classification or listing for hazardous waste. Never dispose of liquid to a landfill. Spilled material should be stabilized or solidified prior to disposal. Once stabilized/solidified, the material may be disposed of through normal means. Certain localities and state laws have specific disposal requirements for non-hazardous industrial chemicals. Consult local municipal authorities, landfill personnel or disposal companies for details prior to any disposal activity. Always follow local, state and federal regulations.

14: TRANSPORT INFORMATION

CE308 Part A: Not hazardous for domestic ground shipment
CE308 Part A IMDG: Limited Quantity not hazardous. Not Regulated.
Bulk Quantity: UN 3082 Environmentally hazardous substance, liquid, n.o.s. (epoxy resin) 9 III MARINE POLLUTANT

Part B: Limited Quantity, Not regulated.
Bulk Quantity: UN 2735 Amines, Liquid, Corrosive, n.o.s. (nonylphenol) 8 II
Part B IMDG: Limited Quantity, Not regulated.
Bulk Quantity: UN 2735 Amines, Liquid, Corrosive, n.o.s. (nonylphenol) 8 II MARINE POLLUTANT - Segregation Group: 18 Alkalis
Placards required over 1,000 lbs.

15: REGULATORY INFORMATION

This product is a "Hazardous Chemical" as defined by the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard Categories	Immediate Hazard	Yes
	Delayed Hazard	Yes
	Fire Hazard	No
	Pressure Hazard	No
	Reactivity Hazard	No
Section 302 Extremely hazardous substance		No
Section 311 Extremely hazardous chemical		Yes

State Regulations This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

16: OTHER INFORMATION

Rating Scale: 0-4

HMIS II ratings: Health = 3, Fire = 1, Reactivity = 2
HMIS III ratings: Health = 3, Fire = 1, Physical Hazard = 2
NFPA ratings: Health = 3, Fire = 1, Reactivity = 2

The information and recommendation in this document are based on the best information available to us at the time of preparation. We make no other warranty, expressed or implied, as to its correctness or completeness, or as to the results or reliance of this product.

This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

User Responsibility: The information in this document cannot be expected to cover all possible individual situations. As the user has the responsibility to provide a safe workplace, all aspects of an individual operation should be examined to determine if, or where, precautions, in addition to those described herein, are required. Any health hazard and safety information herein should be distributed to customers or employees as applicable.

17: DISCLAIMER

The information contained herein is, to the best of our knowledge and belief, accurate and current as of the date of this MSDS. However, since the conditions of handling and use are beyond our control, we make no guarantee of results and assume no liability for damages incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Final determination of suitability of the chemical is the sole responsibility of the user. No representation or warranties, either expressed or implied, as to its correctness or completeness, or as of merchantability, fitness for a particular purpose, or any other nature are made hereunder with respect to the information contained herein or the chemical to which the information refers or as to the results or reliance of this product. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.

END OF MSDS DOCUMENT



1-866-767-6374 | www.dricore.com

© AGT Products (IP) Inc. All rights reserved. DRICORE™ is a trademark of AGT Products (IP) Inc. Used under license by AGT Products Inc. and AGT Products (USA) Inc.